# SAFETY DATA SHEET

## 1. Product and Company Identification

Product identifier TOTAL K.O.-STAINLESS STEEL CLEANER

Other means of identification

Not available

Recommended use

Stainless steel acid cleaner

**Recommended restrictions** 

None known.

Manufacturer

D.L. INDUSTRIAL SUPPLIES

ONTARIO, KOA 1MO

Tel.: 1 888-214-3207 - Cell.: 613 884-3207

www.totalko.ca

Emergency Phone only, 24 hours: (613) 996-6666 (CANUTEC)

### 2. Hazards Identification

GHS classification in accordance with: (CAN) WHMIS 2015

Physical hazardsCorrosive to metalsCategory 1Health hazardsEye damage/irritationCategory 1Skin corrosion/irritationCategory 1AAcute Toxicity/inhalationCategory 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement May be corrosive to metals

Causes severe skin burns and eye damage

Fatal if inhaled

**Precautionary statement** 

Prevention

Keep only in original container. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection.

**Response** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES**: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Immediately call a POISON CENTER/doctor.Specific treatment is urgent(see this label). Specific treatment is(see this label). Wash contaminated clothing before

reuse. Absorb spillage to prevent material damage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in a

corrosive resistant container or a container with resistant inner liner.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3. Composition/Information on Ingredients

MixtureChemical nameCommon name and synonymsCAS number%Sulfuric acid7664-93-915 - 402-Butoxyethanol111-76-21 -5

	4. First Aid Measures			
Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call poison center/doctor/.			
Skin contact	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shows Wash contaminated clothing before reuse. Specific treatment (see product label). Immediately call poison center/doctor/.			
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present an easy to do. Continue rinsing. Immediately call a poison center/doctor.			
Ingestion Most important symptoms/effects, acute and delayed	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor/. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.  Provide general supportive measures and treat symptomatically. Symptoms may be delayed.  Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children.			
Indication of immediate medical attention and special treatment needed				
General information				
	5. Fire Fighting Measures			
Suitable extinguishing media	Treat for surrounding material.			
Unsuitable extinguishing media	Use appropriate extinguisher, as surrounding material.			
Specific hazards arising from the chemical	Firefighters should wear a self-contained breathing apparatus.			
Special protective equipment and precautions for	Firefighters should wear full protective clothing including self contained breathing apparatus.			
firefighters Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.			
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.			
Hazardous combustion products	May include and are not limited to: Sulfur oxide.			
Explosion data Sensitivity to mechanical impact	Not available.			
Sensitivity to static discharge	Not available.			
	6. Accidental Release Measures			
Personal precautions, protective equipment and emergency procedures	spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breath			
Methods and materials for	Should not be released into the environment.			
containment and cleaning up	Large Spills: Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb spillage to prevent material damage. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.			
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS Prevent entry into waterways, sewers, basements or confined areas.			
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.			
	7. Handling and Storage			
Precautions for safe handling	Use only with adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. Avoid breathing vapors or mists of this product. DO NOT get in eyes, on skin or clothing.			

Conditions for safe storage, including any incompatibilities

Store locked up. Store in corrosive resistant container with a resistant inner liner. Keep only in the original container. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure Controls/Personal Protection

#### Occupational exposure limits

Components Value

Sulfuric acid  $TWA \ 8 \ Hr = 1 \ mg/m^3, 15 \ mins \ STEL = 3 mg/m^3$ 2-Butoxyethanol  $TWA : Maximum \ concentration : 20 \ ppm \ ACGIH$ 

Biological limit values Appropriate engineering

No biological exposure limits noted for the ingredient(s).

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Hand protection

Chemical splash goggles.

Skin protection

Chemical resistant gloves. Confirm with a reputable supplier first.

Other

Wear appropriate chemical resistant clothing. As required by employer code. Where exposure

**Respiratory protection** guideline levels may be exceeded, use an approved NIOSH respirator.

Not applicable.

Thermal hazards General hygiene

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands before breaks and immediately after handling

the product.

### 9. Physical and Chemical Properties

AppearanceClearPhysical stateLiquid.FormLiquidColorClear

Odor Solvent odor
Odor threshold Not available.

**pH** 1.0

Melting point/freezing point Not available
Initial boiling point and boiling Not available

range

Pour pointNot available.Partition coefficientNot available

(n-octanol/water)

Flash point > 94 °C

Evaporation rate Not available

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available

Flammability limit - upper

Not available

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available. Vapor pressure Not available Vapor density Not available Relative density 1.10 - 1.15Solubility(ies) Complete **Auto-ignition temperature** Not available

**Decomposition temperature** Not available. Not available. Viscosity

10. Stability and Reactivity

Alcalis. This product may react with oxidizing agents. Reactivity

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Chemical stability Stable under recommended storage conditions.

Conditions to avoid Reacts with strong alcaline product This product may react with oxidizing agents.

Incompatible materials Alcalins products

Hazardous decomposition

products

May include and are not limited to: sulfur oxide.

# 11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Causes digestive tract burns. Ingestion

Prolonged inhalation may be harmful. Inhalation

Skin contact Causes severe skin burns. Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

**Acute toxicity** 

Components **Species Test Results** Sulfuric acid

Acute

2140 mg/kg Oral LD 50 Rat

Inhalation LC 50 510 mg/m<sup>3</sup> ( 2 heures ) Rat Severe irritant

Rabbit Dermal

2-Butoxyethanol

Acute

Oral LD50 Rat 1300 mg/kg Dermal LD50 > 2000 mg/kg Rat

Skin corrosion/irritation Causes severe skin burns and eye damage.

Not available. **Exposure minutes** Erythema value Not available. Oedema value Not available.

Serious eye damage/eye

irritation

Causes serious eye damage.

Iris lesion value Not available.

Conjunctival reddening value

Not available.

Conjunctival oedema value Not available.

Recover days Not available. Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**Non-hazardous by WHMIS/OSHA criteria. **Mutagenicity**Non-hazardous by WHMIS/OSHA criteria.

**Carcinogenicity** None

**Reproductive toxicity**Non-hazardous by WHMIS/OSHA criteria. **Teratogenicity**Non-hazardous by WHMIS/OSHA criteria.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

**Chronic effects** Prolonged inhalation may be harmful.

Further information Not available.

Name of Toxicologically Not available.

**Synergistic Products** 

# 12. Ecological Information

#### **Ecotoxicity**

Components	Species	Test Results Harmful to aquatic organisms	
Sulfuric acid	Avoid contaminating waterways		
2-Butoxyethanol	LC50 Fish (Rainbow Trout) ( 96 hours)	1474 mg/l	
	EC50 Daphnia magna ( 48 hours )	1550 mg/l	
	EC50 Algae (72 hours)	1840 mg/l	

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available

No data available

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone

creation potential, endocrine disruption, global warming potential) are expected from

this component.

# 13. Disposal Consideration

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

### 14. Transport Information

General Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the

Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the

product will appear below.

#### U.S. Department of Transportation (DOT)

**Basic shipping requirements:** 

UN number UN 2796

**Proper shipping name** Sulphuric acid, with not more than 51 % acid

Hazard class 8
Packing group II

#### Transportation of Dangerous Goods (TDG - Canada)

**Basic shipping requirements:** 

UN number UN 2796

**Proper shipping name** Sulphuric acid, with not more than 51 % acid

Hazard class 8
Packing group II

# 15. Regulatory Information

#### Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

WHMIS status Controlled


WHMIS classification

WHMIS labeling


Class E - Corrosive Material



## 16. Other Information







## Disclaimer

The data contained in this material safety data sheet was obtained from sources that were technically accurate, reliable, and state of the art when this document was prepared. If data was unavailable to complete certain sections, the absence of that data is identified in this document. Because the supplier cannot know the exact circumstances during actual use of this product, other hazards, exposure scenarios, disposal considerations, and regulations may apply and it is the responsibility of the user to read and understand the product label and this document before use. Do not use the product for purposes other than those stated in Section 1.

Issue dateJanuary 31, 2018Effective dateJanuary 31, 2018

Version 1.0

Further information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.

Prepared by Unica Canada inc. Phone Number: (450) 655-8168

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of

Chemicals (GHS).